

CUSTOM



1 a 2 Colores | Inkcups Ø60 a 140 mm | Inktrays 100x100 a 150x250mm

PRODUCT DESCRIPTION

Todo Impresión's standard pad printing machine series. It perfectly combines robustness, reliability and versatility. Find out why it is the most chosen model!



FEATURES

- 1 or 2 Colors
- Ink cups from Ø60 up to 140 mm
- Inktrays up to 150 x 250 mm
- Quick change system for ink/plate assembly
- LED lighting
- Tampoprinting under neckline (optional)
- Easy to Automate

TECHNICAL DATA

Cycle	Single, multiple and continuous
Part counter	Yes, sequential and regressive
Speed adjustment	Yes and delay settings
Speed	up to 3.000 p/h (depending on inkwells and options)
Variable buffer stroke	30-100 mm
Maximum tampon height	95 mm
Pressure force	750 N
Drive	Electropneumatic
Control	PLC and 4.3" Color Touch Screen
Control Voltage	24V DC
Feeding	230V / 1 Phase / N / Ground - 50/60 Hz
Electric Consumption	2A
Compressed air	Drying and Filtering 5-6 bar
Air Consumption	75 l/min
Dimensions	L850xW400xH1500mm
Weight	100 kg

SECURITY

- Emergency Shutdown
- Soft start valve
- Double pneumatic safety relief valve with limit switch sensor
- Safety door sensors with coded magnets
- Safety Relay



QUALITY

- Designed for industry according to European standards
- Parts machined in our machining centers
- Laser cut and CNC bent structure
- Original pneumatics of leading brands
- Position sensors for non-contact actuators

VIDEO

La información detallada en el presente documento es únicamente a título informativo, puede contener errores y no tiene ningún carácter contractual.