

ROTAX



Up to 6 Colors : Width 200mm : 4 Lines

PRODUCT DESCRIPTION

Rotary tampon printing machine for caps and/or similar products. Combines automatic loading, cap blocking, flaming, printing, drying and automatic unloading in a single machine. Its ease of start-up, production speed and stability make it an economical solution for large capping productions.



FEATURES

- 1 or 2 Colors
- Automatic loading system with sorter and mechanical insertion of stoppers
- Flamer with electronic ignition
- Antistatic cleaning system
- Automatic drying system after printing
- Plug cleaner
- Automatic ink pumping system
- Automatic download

TECHNICAL DATA

Cycle	Single, multiple and continuous
Part counter	Yes, sequential and regressive
Speed adjustment	Yes
Speed	20K to 80K p/h depending on product and configuration
Maximum tampon height	100 mm
Pressure force	750 N
Drive	Engine
Control	PLC and 5" Color Touch Screen
Control Voltage	24V DC
Feeding	230V / 1 Phase / N / Ground - 50/60 Hz
Electric Consumption	12A
Compressed air	Drying and Filtering 5-6 bar
Air Consumption	75 l/min
Gas	Propane 2 bar
Dimensions	L2500xW2000xH2300mm
Weight	950 kg

QUALITY

- Designed for industry according to European standards
- Parts machined in our machining centers
- Laser cut and CNC bent structure
- Original electronics and pneumatics of leading brands



SECURITY

- Emergency Shutdown
- Soft start valve
- Double pneumatic safety relief valve with limit switch sensor
- Safety door sensors with coded magnets
- Safety relay

VIDEO

La información detallada en el presente documento es únicamente a título informativo, puede contener errores y no tiene ningún carácter contractual.